



Millennium Power Manufacturing Corp.

<http://www.mpmc-china.com>

MTG135PLS-1(1006TAG)

Trailer Generating set Technical Data Sheet



NO:MPT201103-07

© 2011 Millennium Power Manufacturing Corp.



ISO9001:2008
MPMC GENERATING SETS



STANDARD SPECIFICATION

General features:

- Composed of Perkins diesel engine and Leroy Somer or Lisite alternator
- 12V DC start motor and storage battery
- Brushless, Self-excited, IP23, insulation class H alternator
- Engine cooling system: water-cooled
- Key start panel control system as standard, digital auto-start panel is optional
- 8-hour operation base tank
- All generator sets are gone through rigorous testing before being released to the market place, including 50% load, 75% load, 100% load , 110% load and all protection function (overspeed stop, high water temperature, low oil pressure, battery charging fail, emergency stop)



Genset Main Technical Data

3-PH, 50Hz@1500RPM, 400/230V (Also Can Be Made According To Customers' Special Requirements)

Genset Model	Genset Specification					Engine Specification				Alternator Model
	kVA		Cons. 100% (L/H)	dB(A) @7m	Tank (L)	Model	Cyl.	Gov.	Asp.	
	ESP	PRP								
MTG135PLS-1	149	135	33.3	65	370	1006TAG	6	E	TCA	LSA 44.2 S75
MTG135PL-1	149	135	33.3	65	370	1006TAG	6	E	TCA	LYG 274D

- 1) Available in various voltages
- 2) ESP=Standby power standby duty, operation under variable load, without overload.
PRP=Prime power continuous duty operation, under variable load, 10% overload permissible 1/12hr.
- 3) E=Electronic speed governor;
M=Mechanical speed governor
- 4) Asp=Aspiration;
NA=Naturally Asp;
TC=Turbocharged;
TW=Turbocharged after cooled;
TCA= Turbocharged air-air after cooled
- 5) Technical data is subject to work test conditions

Reliable Performance

Voltage regulation

Voltage regulation maintained within $\pm 0.5\%$ as follow:

- Power factor Between 0.8~1.0 lag
- From no load to full load, any steady load
- Speed droop variation under 4.5%

Frequency/Speed undulation

- Change load from 0-100%, Frequency/Speed Droop Ratio within 5%.
- Load from 25-100%, any steady load Frequency/Speed undulation within 0.25%


Effect factor of telecom

- TIF(MA MG1-22) better than 50
- THF(BS EN60034) better than 2%

Criterion

- ISO8528, GB/T2820
- EN12601:2001, EN60034-22:1997, EN60204-1:2006
- ISO9001:2000 Quality Control System

Dimension and Weight



Overall size (L*W*H)

4500*1900*2200

Weight: 2050kg

ENGINE SPECIFICATION

Perkins Diesel Engine

Technical Data

Engine Model	1006TAG
Emissions statement	--
Number of Cylinders	6
Cylinder arrangement	Vertical in-line
Cycle	Four stroke
Aspiration	Turbocharged air-air cooled
Bore×Stroke (mm×mm)	100 x 127
Displacement (Liter)	5.99
Compression Ratio	17.0:1
Prime Power/Speed (kW/rpm)	121/1500
Standby Power/Speed (kW/rpm)	133.5/1500
Speed Governor	Electrical
Cooling System	Water-cooled
Speed Stability (%)	≤5%
Total lubrication system capacity (L)	19.0
Coolant capacity (inc. radiator) (L)	37.22
Fuel Consumption at 100% Load (L/Hr)	33.3(at 1500RPM)
Starter Motor	12 V
Alternator	12 V

Alternator SPECIFICATION

Leroy Somer Alternator (Standard)

Lisite Alternator (Option)

Technical Data

Alternator Model	LSA 44.2 S75 (Leroy Somer) LYG 274D (Lisite)
Exciter type	Brushless, Self-excited
Power factor	0.8
Voltage Adjust range	≥5%
Voltage Regulation NL-FL	≤±0.5%
Insulation Grade	H
Protection Grade	IP23

Control System

1. Standard: Deep Sea DSE3110 Digital Auto Start

Providing the standard functions as follows:

(Also can be made according to the customers' special requirements)

- * Start/Stop controller
- * Ampere meter and selector switch
- * Voltmeter
- * Frequency meter/ Water temperature gauge/ Oil pressure gauge/ Hour counter/ Battery voltage meter
- * Emergency stop pushbutton
- * Alarm System: Over speed、High Engine Temperature
Low Oil Pressure、Charge Fail
- * Protection System: Over speed、High Engine Temperature、Low Oil Pressure、Emergency Stop. And the other protection function pre-setting

2. Option: MP170HC Key Start

3. Option: Smartgen HGM6120 Digital Auto Start (Option assembled with the ATS)

4. Option: Deep Sea DSE7210 Digital Auto Start

5. Option: Deep Sea DSE7220 Digital Auto Start (Option assembled with the ATS)

Digital Auto-start Generator controller integrating digital, intelligent and network techniques is used for automatic control system of diesel generator. It can carry out functions including automatic start/stop, data measure and alarming. Optionally assembled with the ATS, it can carry out auto-switching between the outer power and generating set power. (AMF)

Functions:

- * Automatic Start/Stop
- * 3 start attempts failure and Automatic Crank Disconnect
- * Parameters display (V/A/Hz/Hour)
- * Engine monitoring and protection
- * Charge alternator exciting and Charge alternator fail alarm
- * Running hour counting
- * Settings can be adjustable via key buttons on front panel



(1)



(2)



(3)



(4)



(5)